

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/764,979	01/26/2004	Joseph Indhiran Vanniasinkam	9136.0005-00	6605
22852	7590 02/28/2006		EXAM	INER
FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER LLP 901 NEW YORK AVENUE, NW WASHINGTON, DC 20001-4413			BLEVINS, JERRY M	
			ART UNIT	PAPER NUMBER
			2883	
			DATE MAILED: 02/28/2006	

Please find below and/or attached an Office communication concerning this application or proceeding.

BL

	Application No.	Applicant(s)				
Office Action Summers	10/764,979	VANNIASINKAM ET AL.				
Office Action Summary	Examiner	Art Unit				
	Jerry Martin Blevins	2883				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication. - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).						
Status						
1) Responsive to communication(s) filed on 09 Fe	bruary 2006 (interview).					
· _ · · · · · · · · · · · · · · · · · ·						
·	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is					
closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.						
		3 3.3. 2.3.				
Disposition of Claims						
4) Claim(s) 1-6,8,10-15 and 17 is/are pending in the application. 4a) Of the above claim(s) is/are withdrawn from consideration. 5) Claim(s) is/are allowed. 6) Claim(s) 1-6,8,10-15 and 17 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/or election requirement.						
Application Papers						
 9) The specification is objected to by the Examiner. 10) The drawing(s) filed on 21 September 2004 is/are: a) accepted or b) objected to by the Examiner. Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a). Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 						
11) The oath or declaration is objected to by the Ex	aminer. Note the attached Office	Action or form PTO-152.				
Priority under 35 U.S.C. § 119						
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 						
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal Pa					

Art Unit: 2883

DETAILED ACTION

Introduction

Applicant's request, formulated in attorney-examiner interview conducted

February 7, 2006 and formalized in subsequent Interview summary form, mail date

February 9, 2006, for reconsideration of the finality of the rejection, of the last Office action is persuasive and, therefore, the finality of that action is withdrawn.

The following Office action replaces the previous Office action (Final Rejection).

The current Office action has the status of **Non-final** Rejection.

Response to Arguments

Examiner accepts amendment to claim 1 as to include the limitations of now cancelled claim 7. Prior objection to claim 8 as containing subject matter lacking in antecedent basis is withdrawn.

Applicant's arguments filed 09/14/2005 with respect to claims 1-9 have been fully considered but they are not persuasive.

With regards to claims 1-9, applicants argue that US Patent to Deng et al., number 6,851,870, does not teach an optical detector offset from the optical axis of an optical fiber. Although the image sensor (31) of Deng is not offset from the optical fiber (20), as indicated by applicants, Deng does teach an optical detector (element 30 (B6), Figures 1-6, and column 7, lines 22-24) offset from the optical axis of an optical fiber (element 20 (B4) inserted in aperture 11, Figures 1-6, and column 4, lines 43-67).

Art Unit: 2883

Applicant's arguments with respect to claims 10-13 and 16 have been considered but are most in view of the new ground(s) of rejection.

Applicant's arguments, see pages 12-14, filed 09/14/2005, with respect to the rejection(s) of claim(s) 14 and 15 under 35 USC 103(a) have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, a new ground(s) of rejection is made in view of new interpretation of applied reference to US Patent to Cohen et al., number 5,631,991. Namely, examiner agrees that the combination of Cohen with Deng in the previous rejection of claims 14 and 15 was improper due to lack of motivation to combine the references. However, after further consideration, examiner believes that there exists no reason to need to combine the references. Cohen teaches all the limitations involved in the original combination. See below in rejections under 35 USC 103(a) section for more details.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1-3 and 17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Cohen in view of US Patent to Eide et al., number 5,031,984, and in view of Deng.

Regarding claim 1, Cohen teaches a receiver optical subassembly (Figure 1 and column 6, lines 59-62), comprising a multimode optical fiber stub (Figure 1, element 7

Page 4

and column 8, lines 29-30) and a lens system (Figure 1, element 3) oriented with respect to the multimode optical fiber stub to focus an optical beam exiting the multimode opal fiber onto an active area of an optical detector (Figure 1, element 4 and column 6, lines 59-62). Cohen does not teach that the fiber stub includes an exit surface polished at an angle with respect to an optical axis of the multimode fiber stub. Eide teaches a receiver optical sub assembly (Figure 9) comprising multimode fiber stub (16), which includes exit surface (Figure 7, element 15) polished at an angle (column 5, lines 17-18) with respect to an optical axis of the multimode fiber stub. It would have been obvious to one of ordinary skill in the art at the time of the invention to polish at an angle the exit surface (as taught by Eide) of the multimode fiber stub of Cohen. The motivation would have been to increase coupling efficiency. Cohen in view of Eide does not teach that the optical detector chip is offset from the optic axis of the multimode optical fiber. Deng teaches a receiver optical sub assembly (column 6, line 39 – column 7, line 27) comprising an optical detector chip (30, column 7, lines 22-24) offset (Figure 1) from the optical axis of a fiber (20). It would have been obvious to one of ordinary skill in the art at the time of the invention to offset (as taught by Deng) the

Regarding claim 2, Cohen in view of Eide and in view of Deng teaches the limitations of the base claim 1. Cohen also teaches that the multimode optical fiber stub is mounted in a stub holder (housing 2). Cohen does not teach that the stub holder is positioned in a receptacle. Deng teaches a receiver optical sub assembly (column 6,

optical detector chip and the multimode optical fiber of Cohen in view of Eide. The

motivation would have been to increase coupling efficiency (column 5, lines 1-15).

line 39 – column 7, line 27) comprising a fiber (Figure 1, element 20), a lens (Figure 4B, element 13), and a detector (Figure 4B, element 30 and column 7, line 24), wherein the fiber is mounted in a holder (Figure 1, element 21) positioned in a receptacle (Figure 1, element A3). It would have been obvious to one of ordinary skill in the art at the time of the invention to position the stub holder of Cohen in a receptacle as taught by Deng. The motivation would have been to allow the connection of the fiber stub to external electrical connections.

Regarding claim 3, Cohen in view of Eide and in view of Deng teaches the limitations of the base claim 2. Cohen also teaches a split sleeve (Figure 1, ferrule 6) positioned over a portion of the multimode optical fiber stub. Cohen does not teach that the multimode optical fiber stub is optically coupled with a single-mode optical fiber. Eide teaches a single-mode optical fiber (14) optically coupled with a multimode optical fiber stub (16). It would have been obvious to one of ordinary skill in the art at the time of the invention to position the split sleeve of Cohen so as to optically couple the multimode optical fiber stub with a single-mode optical fiber, as taught by Eide. The motivation would have been to effectively couple light from a light source through the small core single-mode fiber to a detector via the large core multimode fiber (Eide column 5, lines 48-62).

Regarding claim 17, Cohen teaches a receiver optical subassembly (Figure 1 and column 6, lines 59-62), comprising a multimode optical fiber stub (Figure 1, element 7 and column 8, lines 29-30) and a lens system (Figure 1, element 3) oriented with respect to the multimode optical fiber stub to focus an optical beam exiting the

multimode opal fiber onto an active area of an optical detector (Figure 1, element 4 and column 6, lines 59-62). Cohen also teaches that the multimode optical fiber stub is mounted in a stub holder (housing 2). Cohen does not teach that the stub holder is positioned in a receptacle. Deng teaches a receiver optical sub assembly (column 6. line 39 – column 7, line 27) comprising a fiber (Figure 1, element 20), a lens (Figure 4B. element 13), and a detector (Figure 4B, element 30 and column 7, line 24), wherein the fiber is mounted in a holder (Figure 1, element 21) positioned in a receptacle (Figure 1, element A3). It would have been obvious to one of ordinary skill in the art at the time of the invention to position the stub holder of Cohen in a receptacle as taught by Deng. The motivation would have been to allow the connection of the fiber stub to external electrical connections. Cohen also teaches a split sleeve (Figure 1, ferrule 6) positioned over a portion of the multimode optical fiber stub. Cohen does not teach that the multimode optical fiber stub is optically coupled with a single-mode optical fiber. Eide teaches a single-mode optical fiber (14) optically coupled with a multimode optical fiber stub (16). It would have been obvious to one of ordinary skill in the art at the time of the invention to position the split sleeve of Cohen so as to optically couple the multimode optical fiber stub with a single-mode optical fiber, as taught by Eide. The motivation would have been to effectively couple light from a light source through the small core single-mode fiber to a detector via the large core multimode fiber (Eide column 5, lines 48-62).

Art Unit: 2883

Claims 4-6 are rejected under 35 U.S.C. 103(a) as being unpatentable over

Cohen in view of Eide and in view of Deng as applied to claim 1 above, and further in view of US Pre Grant Publication to Richard et al., number 2004/0159776.

Regarding claims 4, Cohen in view of Eide and in view of Deng teaches the limitations of the base claim 1. Cohen does not teach that the lens is mounted on a lens cap, the lens cap being further mounted on a TO header so that the beam is focused on an active area of a detector chip mounted on the TO header. Richard teaches a receiver optical sub assembly (Figure 12b, element 241) comprising a lens (element 210, included in window 208, Figure 12a, page 9, paragraph 73) mounted on a lens cap (206), the cap being mounted on a TO header (header 202 with TO pins 204a-d, Figures 12a, 9a) so that the beam is focused on an active area of a detector chip (Figure 12a, element 214) mounted on the TO header. It would have been obvious to one of ordinary skill in the art at the time of the invention to mount the lens of Cohen in a lens cap further mounted on a TO header as taught by Richard. The motivations would have been to protect the lens and to connect the assembly to external electrical connections using the TO pins of the header (page 1, paragraph 8).

Regarding claim 5, Cohen in view of Eide and in view of Deng teaches the limitations of the base claim 1. Cohen does not teach that the lens is a ball lens. Richard teaches a receiver optical sub assembly comprising a ball lens (element 210, included in window 208, Figure 12a, page 9, paragraph 73) mounted on a lens cap, the cap being mounted on a TO header so that the beam is focused on an active area of a detector chip mounted on the TO header. It would have been obvious to one of

ordinary skill in the art at the time of the invention to use a ball lens as taught by Richard as the lens of Cohen. The motivation would have been to provide an economic focusing system.

Regarding claim 6, Cohen in view of Eide and in view of Deng teaches the limitations of the base claim 1. Cohen does not teach that the detector includes an avalanche photo diode. Richard teaches a receiver optical sub assembly comprising a ball lens mounted on a lens cap, the cap being mounted on a TO header so that the beam is focused on an active area of an avalanche photo diode detector chip (Figure 12a, element 214) mounted on the TO header. It would have been obvious to one of ordinary skill in the art at the time of the invention to include in the optical detector of Cohen an avalanche photo diode as taught by Richard. The motivation would have been to increase receiver sensitivity (page 1, paragraph 5).

Claim 8 is rejected under 35 U.S.C. 103(a) as being unpatentable over Cohen in view of Eide and in view of Deng as applied to claim 1 above, and further in view of US Patent to Kato et al., number 5,737467.

Regarding claim 8, Cohen in view of Eide and in view of Deng teaches the limitations of the examiner treated base claim 7. Cohen does not teach that the angle is about 8 degrees. Kato teaches an optical assembly (Figure 5a) comprising a fiber (140) and a detector (131) wherein the fiber is polished at an angle of about 8 degrees (column 10, lines 27-33). It would have been obvious to one of ordinary skill in the art at the time of the invention to form the angle of Cohen in view of Eide at about 8 degrees,

Page 9

Art Unit: 2883

as taught by Kato. The motivation would have been to reduce reflection light (column 10, lines 31-32).

Claims 10-13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Eide in view of Cohen.

Regarding claim 10, Eide teaches a method for receiving light in a receiver optical sub assembly (Figure 9) comprising coupling a light beam (column 5, lines 48-62 and column 6, lines 15-23) from a single-mode optical fiber (Figure 9, element 14) into a multimode fiber stub (Figure 9, element 16) and focusing the light beam (using lens 36, Figure 9) onto an active area of an optical detector (Figure 9, element 30 and column 7, line 13). Eide also teaches a single-mode optical fiber (14) optically coupled with a multimode optical fiber stub (16). Edie does not teach a sleeve wherein the sleeve aligns the single-mode optical fiber and the multi-mode fiber stub. Cohen teaches a sleeve (Figure 1, ferrule 6) positioned over a portion of a multimode optical fiber stub. It would have been obvious to one of ordinary skill in the art at the time of the invention to position the sleeve of Cohen so as to optically couple the multimode optical fiber stub with a single-mode optical fiber, as taught by Eide. The motivation would have been to effectively couple light from a light source through the small core single-mode fiber to a detector via the large core multimode fiber (Eide column 5, lines 48-62).

Regarding claim 11, Eide in view of Cohen teaches the limitations of the base claim 10. Eide also teaches that the method includes providing an angled exit surface on the multimode fiber stub (Figure 7, element 15 and column 5, lines 14-15) and

positioning the active area of the optical detector (30) to compensate for the angled exit surface (column 6, lines 59-63).

Regarding claim 12, Eide teaches a receiver optical sub assembly (Figure 9) comprising means for receiving a light beam into a multimode fiber stub (by coupling a light beam from a single-mode optical fiber 14 into a multimode fiber stub 16, column 5, lines 48-62 and column 6, lines 15-23) and means for focusing the light beam (using lens 36) onto an active area of an optical detector (30). Eide also teaches a single-mode optical fiber (14) optically coupled with a multimode optical fiber stub (16). Edie does not teach a sleeve wherein the sleeve aligns the single-mode optical fiber and the multi-mode fiber stub. Cohen teaches a sleeve (Figure 1, ferrule 6) positioned over a portion of a multimode optical fiber stub. It would have been obvious to one of ordinary skill in the art at the time of the invention to position the sleeve of Cohen so as to optically couple the multimode optical fiber stub with a single-mode optical fiber, as taught by Eide. The motivation would have been to effectively couple light from a light source through the small core single-mode fiber to a detector via the large core multimode fiber (Eide column 5, lines 48-62).

Regarding claim 13, Eide in view of Cohen teaches the limitations of the base claim 12. Eide also teaches means for increasing the return loss characteristics of the receiver optical sub assembly. Specifically, Eide teaches a multimode fiber stub (16), which includes exit surface (Figure 7, element 15) polished at an angle (column 5, lines 17-18) with respect to an optical axis of the multimode fiber stub.

Claim 14 is rejected under 35 U.S.C. 103(a) as being unpatentable over Cohen in view of Richard.

Cohen teaches a method of assembling a receiver optical sub assembly (Figure 1 and column 6, lines 59-62) comprising: press fitting a multimode fiber stub (Figure 1. element 7) into a stub holder (ferrule 6), positioning a split sleeve (part of housing 2 extending along ferrule 6) over a portion of the multimode fiber stub, press fitting the stub holder into a receptacle (of which the entrance is labeled as element 10), focusing light received form a lens system (Figure 1, element 3) onto an active area of a detector chip (Figure 1, element 4 and column 6, lines 59-62), actively aligning the active area of the detector chip with respect to the multimode fiber stub (column 2, lines 63-67), and positionally fixing the active area of the detector chip with respect to the multimode fiber stub (column 2, lines 63-67). Cohen does not teach the steps of positioning a lens system in a lens cap, positioning a detector chip onto a header, and mounting the lens cap to the header. Richard teaches a receiver optical sub assembly (Figure 12b, element 241) comprising a lens (element 210, included in window 208, Figure 12a, page 9, paragraph 73) positioned in a lens cap (206), the cap being mounted on a header (header 202 with TO pins 204a-d, Figures 12a, 9a) so that the beam is focused on an active area of a detector chip (Figure 12a, element 214) positioned onto the header. It would have been obvious to one of ordinary skill in the art at the time of the invention to position the lens of Cohen in a lens cap further mounted on a header and to position a detector chip onto the header as taught by Richard. The motivations would have been to protect the lens, to integrate the assembly, and to connect the assembly

to external electrical connections using the TO pins of the header (page 1, paragraph 8).

Page 12

Claim 15 is rejected under 35 U.S.C. 103(a) as being unpatentable over Cohen in view of Richard as applied to claim 14 above, and further in view of Eide.

Cohen in view of Richard teaches the limitations of the base claim 14. Cohen does not teach that the step of positionally fixing the active area includes epoxying the header to the receptacle. Eide teaches a method of assembling a receiver optical sub assembly comprising the step of positionally fixing the active area of a detector chip with respect to a multimode fiber using epoxy (column 6, lines49-56). It would have been obvious to one of ordinary skill in the art at the time of the invention to use epoxy, as taught by Eide, as the tool for positionally fixing the active area taught by Cohen in view of Deng and Richard. The motivation would have been to obtain a secure, economic bond.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Jerry Martin Blevins whose telephone number is 571-272-8581. The examiner can normally be reached on Monday through Friday.

Art Unit: 2883

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Frank G. Font can be reached on 571-272-2415. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

JMB

Frank G. Font
Supervisory Patent Examiner
Technology Center 2800

Frank Il Fort

Page 13